

ERIE WATER TREATMENT
Bannerlaan 83E,
B-2280 Grobbendonk - Belgium
T +32 (0)14 28 51 71
infobelgium@eriewatertreatment.com

**MEMBERSHIPS** 



















## **TECHNICAL SPECIFICATIONS**

MODEL	IQ-WHF-AC
Operating pressure min/max (bar)	2,0 / 8,3
Operating temperature min/max (°C)	2 / 48
Electrical Connection (V / Hz)	230 / 50 (1)
Max. power consumption (VA)	8
Hydraulic connection inlet/outlet	1" BSP Male

# PERFORMANCES (2)

MODEL	IQ-WHF-AC			
FILTER MEDIA (LTR)	12	26	44	
Recommanded maximum service flow (m³/hr) <sup>(3)</sup>	1,0	1,2	1,4	
Backwash flow rate (Ltr/min)	19			
Rinse water usage per regeneration (Ltr) <sup>(4)</sup>		132		

### **DIMENSIONS & WEIGHTS**

MODEL	IQ-WHF-AC		
FILTER MEDIA (LTR)	12	26	44
System depth (pressure tank & valve) (mm)		371	
System height (mm)	629	1065	1554
Weight (kg)	12,0	23,0	37,0

#### **FEATURES & BENEFITS:**

**USER-FRIENDLY** 

- Multilingual software.
- Legible display.
- Easy programming.
- No need for maintenance & no filter replacement is needed.

#### RELIABLE WATER TREATMENT

- Activated carbon as a natural and one of the most reliable ways of filtering water.
- · Provide color and odor-free water.
- Remove chemical contamination from the water such as chlorines, residues of pesticides and herbicides.
- Remove all particles larges than 0,04 mm and extend the lifespan of water-using appliances.

#### **ACCESSORIES:**

- Voltage transformer 230-24V
- 1" BSP male in/out connection kit
- 3 mtr reinforced drain hose with 2 clamps
- Air gap with double drain connection